Opener Guide

Innovative features.
Easy programming.
Universal rail systems.

The Genuine. The Original.

OVERHEAD DOOR®

OHD**ANYWHERE**®
SMART DEVICE ENABLED GARAGE DOOR CONTROLLER

The OHD Anywhere® system allows you to control and monitor your sectional garage door from almost anywhere. Controlled through the free app on Google Play or Apple App Store®, this technology is available as an integrated feature in certain Overhead Door® garage door openers or as an external kit. The kit allows homeowners to retrofit any Overhead Door® opener or most other brands made after 1993 with functioning safety photo eyes. It comes equipped with extensive time-based rules and notification features, allowing account holders to easily customize based on their needs and manage accessibility for each add-on user.

Product features

- Control and monitor the state of your garage door from anywhere with your smart device
  - Compatible with most iOS and Android mobile devices
  - Allows monitoring through the OHD Anywhere® app as to whether the door is opened or closed by the opener

- Remote access control system with fast and easy set-up

- Ability to know if an authorized user is operating the door with the OHD Anywhere® app
  - Maintains access history report for each opener

- UL 325 compliant – audible and visual signals before door moves when operated from smart device

- Use the OHD Anywhere® app to control any combination of 20 different Overhead Door® Wi-Fi integrated garage door openers or external OHD Anywhere® kits

Virtual keys

- Create a virtual key to grant temporary or permanent access to relatives, friends, or service workers – up to 20 total users

Time-based features

- Set the door to automatically close at a specific time each day

- Program to automatically close the garage door after a set time frame of continuously being open

Note

External kit compatible with all Overhead Door® and most other residential garage door opener brands that use photo-eye sensors. Visit **overheaddoor.com/ohdanywhere** for compatibility details.

OPEN
DOOR

Compatible with:

WORKS WITH
alexa

works with
Google Assistant

ALARM.COM

PLAYS WITH
YONOMI

Control4

BenchSentry™
Hide it. Secure it. Watch it.

clare

URC

SmartThings

See our website for a complete list of smart home system partners.

Infinity™ *2000*

SAFE-T-PULSE™ TECHNOLOGY

Quiet, powerful and compact wall mount design

MODEL 9020H/9020H-B

Direct drive wall mount

LED light fixture

- **Safe-T-Pulse™ System –** Patent-pending system using electronic pulses during initial door travel to detect slack cables & stop unsafe operation if necessary.
- 24V DC motor
- Opening speed: Up to 7.5 in/second†
- LED light fixture included
- Limited Lifetime motor warranty
- For residential sectional doors up to 14' high and 850 lbs
- CodeDodger® access security system
- Includes door lock
- 6' power cord standard
- **Can be ordered with (9020H-B) or without (9020H) integrated battery backup**

MODEL 9120H/9120H-B

Direct drive wall mount   OHD**ANYWHERE**®

LED light fixture

- **Integrated Wi-Fi with OHD Anywhere®**
- **Safe-T-Pulse™ System –** Patent-pending system using electronic pulses during initial door travel to detect slack cables & stop unsafe operation if necessary.
- 24V DC motor
- Opening speed: Up to 7.5 in/second†
- LED light fixture included
- Limited Lifetime motor warranty
- For residential sectional doors up to 14' high and 850 lbs
- CodeDodger® access security system
- Includes door lock
- 6' power cord standard
- **Can be ordered with (9120H-B) or without (9120H) integrated battery backup**

Destiny® *1500*

Power, speed, intelligence and convenience

MODEL 8060H/8060H-B

Direct screw drive

- 140V DC motor
- Opening speed: Up to 12.0 in/second†
- Maintenance free screw drive rail
- Limited lifetime motor and screw drive rail warranty *
- For residential sectional doors up to 14' high; one-piece doors up to 8' high
- Motion detector lighting
- Bright lighting with capacity for (2) OHD LED Bulbs (recommended); or 100 watt incandescent or CFL bulbs
- CodeDodger® access security system
- Available for use with heavy-duty rail
- 6' power cord standard
- **Can be ordered with (8060H-B) or without (8060H) integrated battery backup**

MODEL 8160H/8160H-B

Direct screw drive   OHD**ANYWHERE**®

- **Integrated Wi-Fi with OHD Anywhere®**
- 140V DC motor
- Opening speed: Up to 12.0 in/second†
- Limited lifetime motor and screw drive rail warranty *
- For residential sectional doors up to 14' high; one-piece doors up to 8' high
- Motion detector lighting
- Bright lighting with capacity for (2) OHD LED Bulbs (recommended); or 100 watt incandescent or CFL bulbs
- CodeDodger® access security system
- Available for use with heavy-duty rail
- 6' power cord standard
- Can be ordered with (8160H-B) or without (8160H) integrated battery backup

† +/- 0.5" per second   * See Operation and Maintenance Manual for details

Destiny® 1200

Quiet yet powerful with the ultimate in convenience

MODEL 8130H/8130H-B

Belt or chain

OHD**ANYWHERE**

- Integrated Wi-Fi with OHD Anywhere®
- 140V DC motor
- Opening speed: up to 9.0 in/second†
- Limited lifetime motor and gearbox warranty *
- For residential sectional doors up to 14' high; one-piece doors up to 8' high
- Motion detector lighting
- Bright lighting with capacity for (2) OHD LED Bulbs (recommended); or 100 watt incandescent or CFL bulbs
- CodeDodger® access security system
- Available for use with heavy-duty rail
- 6' power cord standard
- **Can be ordered with (8130H-B) or without (8130H) integrated battery backup**

Odyssey® 1000
Quiet yet powerful performance

MODEL 7030H/7030H-B	MODEL 7130H/7130H-B

Belt or chain drive

Belt or chain drive   **OHD** *ANYWHERE*

- 140V DC motor
- Opening speed: Up to 7.5 in/second†
- Limited lifetime motor and gearbox warranty*
- For residential sectional doors up to 14' high; one-piece doors up to 8' high
- Bright lighting with capacity for (2) OHD LED Bulbs (recommended); or 100 watt incandescent or CFL bulbs
- CodeDodger® access security system
- Available for use with heavy-duty rail
- 6' power cord standard
- **Can be ordered with (7030H-B) or without (7030H) integrated battery backup**

† +/- 0.5" per second   * See Operation and Maintenance Manual for details

- **Integrated Wi-Fi with OHD Anywhere®**
- 140V DC motor
- Opening speed: Up to 7.5 in/second†
- Limited lifetime motor and gearbox warranty*
- For residential sectional doors up to 14' high; one-piece doors up to 8' high
- Bright lighting with capacity for (2) OHD LED Bulbs (recommended); or 100 watt incandescent or CFL bulbs
- CodeDodger® access security system
- Available for use with heavy-duty rail
- 6' power cord standard
- **Can be ordered with (7130H-B) or without (7130H) integrated battery backup**

Legacy® 920

Flexible platform with power and reliability

Belt or chain drive

OHD**ANYWHERE**.

- Integrated Wi-Fi with OHD Anywhere®
- 24V DC motor provides quiet operation
- Opening speed: Up to 7.0 in/second†
- Limited Lifetime motor and integrated gearbox limited warranty*
- For residential sectional doors up to 10' high
- Bright lighting with capacity for (2) OHD LED Bulbs (recommended); or 60 watt incandescent or CFL bulbs
- C-channel rail for strength and aesthetics
- CodeDodger® access security system
- 6' power cord standard
- Available for use with heavy-duty rail
- Can be ordered with (7120H-B) or without (7120H) optional integrated battery backup
- Can be ordered with (7120HL/7120HL-B) integrated LED lighting

California Residents:
As required by California State Law SB-969, all newly installed openers must have battery backup as of 07/01/2019.

† +/- 0.5" per second   * See Operation and Maintenance Manual for details

Legacy® 850

Power, value and reliability

MODEL 2029/2029B	MODEL 2129/2129B

Belt or chain drive

Belt or chain drive   OHD**ANYWHERE**.

- 24V DC motor
- Opening speed: Up to 7.0 in/second†
- 10 year motor and integrated gearbox limited warranty*
- For residential sectional doors up to 10' high
- DC motor for quiet operation and lighter handling
- Standard lighting with capacity for (1) OHD LED Bulb (recommended); or 60 watt incandescent or CFL bulb
- C-channel rail for strength and aesthetics
- CodeDodger® access security system
- Available for use with heavy-duty rail
- Can be ordered with (2029B) or without (2029) optional battery backup at time of purchase only. Battery cannot be added later

- **Integrated Wi-Fi with OHD Anywhere®**
- 24V DC motor
- Opening speed: Up to 7.0 in/second†
- 10 year motor and integrated gearbox limited warranty*
- For residential sectional doors up to 10' high
- DC motor for quiet operation and lighter handling
- Standard lighting with capacity for (1) OHD LED Bulb (recommended); 60 watt incandescent or CFL bulb
- C-channel rail for strength and aesthetics
- CodeDodger® access security system
- Available for use with heavy-duty rail
- Can be ordered with (2129B) or without (2129) optional battery backup at time of purchase only. Battery cannot be added later

Legacy® 650
Value and reliability

Belt or chain drive

- 24V DC motor
- Opening speed: Up to 6.5 in/second†
- 5 year motor and integrated gearbox limited warranty*
- For residential sectional doors up to 8' high
- DC motor for quiet operation and lighter handling
- Standard lighting with capacity for (1) OHD LED Bulb (recommended); or 60 watt incandescent or CFL bulb
- C-channel rail for strength and aesthetics
- CodeDodger® access security system
- Available for use with heavy-duty rail
- **Can be ordered with (1029) or without (1029B) optional battery backup at time of purchase only. Battery cannot be added later**

† +/- 0.5" per second   * See Operation and Maintenance Manual for details

Belt or chain drive   OHD**ANYWHERE**

- **Integrated Wi-Fi with OHD Anywhere®**
- 24V DC motor
- Opening speed: Up to 6.5 in/second†
- 5 year motor and integrated gearbox limited warranty*
- For residential sectional doors up to 8' high
- DC motor for quiet operation and lighter handling
- Standard lighting with capacity for (1) OHD LED Bulb (recommended); or 60 watt incandescent or CFL bulb
- C-channel rail for strength and aesthetics
- CodeDodger® access security system
- Available for use with heavy-duty rail
- **Can be ordered with (1129B) or without (1129B) optional battery backup at time of purchase only. Battery cannot be added later**

California Residents:
As required by California State Law SB-969, all newly installed openers must have battery backup as of 07/01/2019.

LIGHT BULBS

Garage door opener LED bulb

Common LED and CFL bulbs can emit interference to limit the range of garage door remotes. Incandescent light bulbs, which are being phased out due to energy inefficiency, can have their lives shortened by vibration associated with opener operation. The Overhead Door™ LED bulb solves these and other problems to ensure the garage door opener light doesn't leave your garage in the dark!

40656R

25,000 hour life

Cold weather tested

Damp location rated

REMOTES AND CONTROLLERS

3-Button Remote Visor/Keychain Style

This remote with auto-seek dual frequency (315/390 MHz) allows you to operate up to 3 openers. It comes with a visor clip and can be used with a key ring. Backward compatible with all CodeDodger® equipped Overhead Door® openers.

37219R

1-Button Remote Visor/Keychain Style

If the remote only needs to operate one opener, you may want our simple, easy-to-use one-button remote. Also features auto-seek dual frequency. Backward compatible with all CodeDodger® equipped Overhead Door® openers.

38502R

OHD Anywhere® Retrofit Kit

Remotely monitor and control your garage door from almost anywhere with your smart device. Check door status and take advantage of time based features and virtual keys for added peace-of-mind and control.

39394R

Multiple Visor Style Remote Options

These remotes feature large buttons with great tactile feel and a clearly visible LED. Multi-directional visor clip lets you decide how the remote will fit on the visor. These remotes use auto-seek dual frequency and are backwards compatible with all CodeDodger ® equipped Overhead Door® openers.

41539U

41539T

41539S

41539R

California Residents:
As required by California State Law SB-969, all newly installed openers must have battery backup as of 07/01/2019.

Wireless Wall Console

Absolutely no wiring required for operation!
No need to have an additional wired wall console.
The delay button allows a user an extra 10 to 30
seconds to exit before the door begins to move.
Works with most Overhead Door® CodeDodger®
equipped openers manufactured since 2013. Not
compatible with Legacy® 800 Model 2026 and
Standard Drive® 600 Model 1026.

39903R

Multi-function Wired Wall Console

Featuring large push buttons for easy operation,
this wired wall console also has our Sure-Lock™
button to disable the remotes and keypad for
extra security at night or while away from home.

39166R

Digital Wireless Keypad

The wireless keypad provides convenient and
secure garage access without the need for a
remote or key. This is an ideal secure access
solution for kids returning from school, when work-
ing on exterior home projects or when going out for
a jog. Also uses auto-seek dual frequency.
(315/390 MHz)

Choose a color for the flip-up cover that best
complements your home.

| White 37227R | Gray 37227S | Tan 37227T | Almond 37227U |

37225R

4-Button Universal Remote

This 4-button universal
remote works with
most major garage
door openers and gate
receiver brands in the
industry! Each button
can be programmed
individually of the others
to multiple manufacturer
combinations. Visor clip
or key chain option inside
every box.

40660R

Universal Wireless Wall Console

Controls multiple
openers from a variety
of manufacturers on a
single wireless console.
Works with most major
rolling and fixed code
brands in the USA. Easy
programming modes
and absolutely no wires
required for operation.

41552R

Universal Wireless Keypad

Works with most major
rolling and fixed code
brands sold in the USA.
Control three different
garage door openers with
a single PIN.

Keypad comes standard in
White and is compatible
with optional lids in
Almond, Gray and Tan.

41250R

Battery Backup Options

Our battery backup options provide reliable
operation when there is a power outage.

Infinity® 2000

Legacy® 920

Destiny® 1200, Destiny® 1500, Odyssey® 1000

41590R

39524R

↑ Battery Backup Option

41152S

Safe-T-Beam® Photo Eyes

Backward compatible with all Overhead
Door® residential openers that use a sensor
system on any door size. Rounded design
helps prevent wayward objects from
accidentally knocking them out of alignment.

37221R

FEATURES	INFINITY™ 2000 MODELS 9020H/9120H-B/9120H/9120H-B	DESTINY® 1500 MODELS 8060H/8060H-B/8160H/8160H-B	DESTINY® 1200 MODELS 8130H/8130H-B
Drive system	Wall Mount	Direct drive screwΔ	Belt or chainΔΔ
Motor	24V DC	140V DC	140V DC
Maximum door weight†	850 lbs	750 lbs	750 lbs
Integrated Wi-Fi with OHD Anywhere®	√ (9120H-B)	√ (8160H)	√
Integrated Battery Backup	√ (9120H-B)	No	No
Drive gear	Direct shaft couple	N/A	Gearbox integrated with motor
Maximum speed	7.5"/second*	12.0"/second*	9.0"/second*
Soft start – soft stop	√	√	√
Auto seek dual frequency (315 or 390 MHz)	√	√	√
DoorDetect™	√	√	√
Power on demand	No	√	√
Power cord standard length	6'	6'	6'
RAIL AND HEIGHTS			
Sectional doors – max height	14'	14'	14'
One piece doors – max height	N/A	8'	8'
Rail type	N/A	C-channel	C-channel
Rail sizes (14'-12' are 2-piece rails, all others 1-piece)	N/A	14-12-10-8-7	14-12-10-8-7 (9' - belt only)
Rail cut-down capability on jobsite	N/A	√	√
Common rail for reduced inventory	N/A	√	√
Rail shrink wrap color mode	N/A	Blue	Red-Belt / Black-Chain
LIGHTING			
Light bulb count		2	2
Light positioned toward inside of garage		√	√
Light bulb compatibility	External LED light fixture	OHD LED recommended; Incandescent	OHD LED recommended; Incandescent
Max combined wattage for incandescent bulbs		200 (2-100W)	200 (2-100W)
Light stays on for 4 min. upon activation	√	√	√
Motion detector lighting	No	√	√
Integrated LED lighting	No	No	No
HOMELINK®/CAR2U®			
HomeLink® compatible	√	√	√
Car2U® compatible	√	√	√
WARRANTY**			
Motor	Limited lifetime	Limited lifetime	Limited lifetime
Rail	N/A	Limited lifetime	15 year limited (belt) / 5 year limited (chain)
Parts	5 year limited	5 year limited	5 year limited
Accessories	1 year limited	1 year limited	1 year limited
ACCESSORIES			
STANDARD			
Remote (operates up to 3 doors except Models 1029 and 1129)	(1) 3-button	(1) 3-button	(1) 3-button
CodeDodger® access security system	√	√	√
Pre-programmed remote	√	√	√
Simple steps to change programming	√	√	√
Wall console	Wireless Wall Console	Multi-function Wired Wall Console	Multi-function Wired Wall Console
Sure-Lock™ control	No	√	√
Safe-T-Beam® photo eyes	Rounded deflective design	Rounded deflective design	Rounded deflective design
OPTIONAL			
Garage door opener LED Bulb	N/A	√	√
Digital Wireless Keypad	√	√	√
Battery Backup	√	√	√
Wireless Wall Console with closing delay function	Standard	√	√
OHD Anywhere® Retrofit Kit	√ (9020H)§	√ (8060H/8060H-B)	Integrated
Heavy-duty Rail	N/A	√	√

Δ Direct motor driven steel screw is self lubricating & requires no maintenance under normal operating conditions.   ΔΔ Steel-reinforced belt or full-length chain.
§OHDAnywhere kit for 9020H includes internal circuit board to be inserted into powerhead.

ODYSSEY® 1000	LEGACY® 920	LEGACY® 850	LEGACY® 650
MODEL 7030H/7030H-B/7130H/7130H-B	MODELS 7120H/7120H-B/7120HL/7120HL-B	MODELS 2029/2029B/2129/2129B	MODELS 1029/1029B/1129/1129B
Belt or chain△△	Belt or chain△△	Belt or chain△△	Belt or chain△△
140V DC	24V DC	24V DC	24V DC
750 lbs	500 lbs	500 lbs	350 lbs
√ (7130H/7130H-B)	√	√ (2129/2129B)	√ (1129/1129B)
No	√ (7120HL-B/7120H-B)	√ (2029B/2129B)	√ (1029B)
Gearbox integrated with motor	Gearbox integrated with motor	Gearbox integrated with motor	Gearbox integrated with motor
7.5"/second*	7.0"/second*	7.0"/second*	6.5"/second*
√	√	√	No
√	√	√	√
√	√	√	√
√	No	No	No
6'	6'	4' (6' model available)	4' (6' model available)
14'	10'	10'	8'
8'	N/A	N/A	N/A
C-channel	C-channel	C-channel	C-channel
14-12-10-8-7 (9' - belt only)	10-8-7 (9' - belt only)	8-7	8-7
√	√	√	√
√	√	√	√
Red-Belt / Black-Chain	Red-Belt / Black-Chain	Red-Belt / Black-Chain	Red-Belt / Black-Chain
2	2	1	1
√	√	√	√
OHD LED recommended; Incandescent	OHD LED recommended; Incandescent	OHD LED recommended; Incandescent	OHD LED recommended; Incandescent
200 (2-100W)	120 (2-60W)	60 (1-60W)	60 (1-60W)
√	√	√	√
No	No	No	No
No	√ (Models 7120HL and 7120HL-B only)	No	No
√	√	√	√
√	√	√	√
Limited lifetime	Limited lifetime	10 year limited	5 year limited
15 year limited (belt) / 5 year limited (chain)	15 year limited (belt) / 5 year limited (chain)	15 year limited (belt) / 5 year limited (chain)	15 year limited (belt) / 5 year limited (chain)
5 year limited	3 year limited	1 year limited	1 year limited
1 year limited	1 year limited	1 year limited	1 year limited
(1) 3-button	(1) 3-button	(1) 3-button	(1) 1-button
√	√	√	√
√	√	√	√
√	√	√	√
Multi-function Wired Wall Console	Multi-function Wired Wall Console	Multi-function Wired Wall Console	Push-button
√	√	√	No
Rounded deflective design	Rounded deflective design	Rounded deflective design	Rounded deflective design
√	√	√	√
√	√	√	√
√	√	Must order B models	Must order B models
√	√	√	√
√ (7030H/7030H-B)	Integrated	√ (2029/2029B)	√ (1029/1029B)
√	√	√	√

* +/- 0.5" per second. Speed will slow with one-piece doors if opener works with that type.   ** See Operation & Maintenance Manual for details.   † Door must be well counter-balanced.

POWERHEAD - BOXED
Shipping-ready packaged dimensions & weights

Opener	Model number	Length	Width	Height	Weight (lbs)
Destiny® 1500	8060H/8160H	19¼"	10¾"	10"	18
Destiny® 1500	8060H-B/8160H-B	19¼″	10¾″	10″	18
Destiny® 1200	8130H	19¼″	10¾″	10″	22
Destiny® 1200	8130H-B	19¼″	10¾″	10″	13
Odyssey® 1000	7030H/7130H	19¼″	10¾″	10″	13
Odyssey® 1000	7030H-B/7130H-B	19¼″	10¾″	10″	17
Legacy® 920	7120H-B/7120HL-B	18½″	16"	8¾″	19¾
Legacy® 920	7120H/7120HL	18½″	16"	8¾″	15½
Legacy® 850	2029	13″	10″	8¾″	12
Legacy® 850	2129B/2029B	19½″	10¼″	9½″	18
Legacy® 850	2129	13″	10¼″	9½″	13
Legacy® 650	1029	13″	10″	8¾″	12
Legacy® 650	1129	13″	10¼″	9½″	12
Legacy® 650	1129B/1029B	19½″	10¼″	9½″	17½
Infinity™ 2000	9020H/9120H	17″	15″	11½″	29½
Infinity™ 2000	9020H-B/9120H-B	17″	15″	11½″	31½

RAIL ASSEMBLIES
Dimensions & weights without packaging

Rail type	Length (inches)	Width (inches)	Height (inches)	Weight (lbs)	Note	Wrap color	Headroom clearance	One-piece door compatible
7' Belt	116³/₈"	2⁷/₈"	1¼"	11.5	1 pc.	Red	1½"	yes
7' Chain	116³/₈"	2⁷/₈″	1¼"	14	1 pc.	Black	1½"	yes
7' Screw	112½"	2⁷/₈″	1¼"	14	1 pc.	Blue	1½"	yes
8' Belt	128³/₈"	2⁷/₈″	1¼"	12	1 pc.	Red	1½"	yes
8' Chain	128³/₈"	2⁷/₈″	1¼"	15	1 pc.	Black	1½"	yes
8' Screw	124¼"	2⁷/₈″	1¼"	15.5	1 pc.	Blue	1½"	yes
9' Belt	140³/₈"	2⁷/₈″	1¼"	13	1 pc.	Red	1½"	no
10' Belt	157⁷/₈"	2⁷/₈″	1¼"	15	1 pc.	Red	1½"	no
10' Chain	157⁷/₈"	2⁷/₈″	1¼"	18	1 pc.	Black	1½"	no
10' Screw	153½"	2⁷/₈″	1¼"	18	1 pc.	Blue	1½"	no
12' Belt	2-91 (182)"	2⁷/₈″	1¼"	18	2 pcs.	Red	1½"	no
12' Chain	2-91 (182)"	2⁷/₈″	1¼"	22	2 pcs.	Black	1½"	no
12' Screw	2-88¾ (172)"	2⁷/₈″	1¼"	23	2 pcs.	Blue	1½"	no
14' Belt	2-103 (206)"	2⁷/₈″	1¼"	20	2 pcs.	Red	1½"	no
14' Chain	2-103 (206)"	2⁷/₈″	1¼"	25	2 pcs.	Black	1½"	no
14' Screw	2-100¾ (201½)"	2⁷/₈″	1¼"	26	2 pcs.	Blue	1½"	no

NOTES:
1. All measurements are approximate and should be verified in field if critical accuracy is needed.
2. Lengths and widths rounded to nearest 1/8". Weights rounded to nearest 1/4 pound.
3. Count per complete pallet:
    Destiny® 1500, Odyssey® 1200, Destiny® 1200, Odyssey® 1000: 32
    Legacy® 920: 30
    Legacy® 850, Legacy® 650: 64
    Infinity® 2000: 24
    Chain/belt rails 7'and 8' lengths: 64
    All other lengths and rail types: 32

POWERHEAD - ONLY
Unit dimensions & weights without packaging

Opener	Model number	Length	Width	Height	Weight (lbs)
Destiny® 1200	8060H/8160H	16⅝"	10"	7⅝"	11
Destiny® 1200	8130H	16⅝"	10"	7¼"	8
Odyssey® 1000	7030H/7130H	16⅝"	10"	7¼"	8
Legacy® 920	7120H-B	11⅜"	20⅜"	5⅞"	13
Legacy® 920	7120H	7⅝"	20⅜"	5⅞"	9
Legacy® 850	2029/2029B/2129/2129B	11"	9⅜"	5½"	8
Legacy® 650	1029/1029B/1129/1129B	11"	9⅜"	5½"	8
Infinity™ 2000	9020H	8¾"	6¾"	12"	17½
Infinity™ 2000	9120H-B	8¾"	6¾"	14½"	21⅓

OVERALL ASSEMBLED POWERHEAD & RAIL ASSEMBLIES

Rail Type	Overall length (inches) Destiny 1500, Odyssey 1200, Destiny 1200, Odyssey 1000	Overall weight (lbs) Destiny 1500, Odyssey 1200	Overall weight (lbs) Destiny 1200, Odyssey 1000	Overall length (inches) Legacy 850, Legacy 650	Overall weight (lbs) Legacy 850, Legacy 650	Overall length (inches) Legacy 920 with BBU	Overall weight (lbs) Legacy 920 with BBU	Overall length (inches) Legacy 920 without BBU	Overall weight (lbs) Legacy 920 without BBU
7' Belt	127"	—	19¾	121¼"	19¼	121⅞"	25¼	118¼"	21
7' Chain	127"	—	25¼	121¼"	21¾	121⅞"	27¾	118¼"	23½
7' Screw	126¾"	25¼	—	—	—	—	—	—	—
8' Belt	139"	—	20¼	133"	19¾	133⅞"	26¼	130¼"	22
8' Chain	139"	—	26¼	133"	22¾	133⅞"	29¼	130¼"	25
8' Screw	138¾"	26¾	—	—	—	—	—	—	—
9' Belt	151"	—	24¼	—	—	145⅞"	27¼	142¼"	23
10' Belt	168½"	—	26¼	—	—	163⅜"	28¾	159¾"	24½
10' Chain	168½"	—	29¼	—	—	163⅜"	31¾	159¾"	27½
10' Screw	167¾"	29¼	—	—	—	—	—	—	—
12' Belt	192½"	—	29¼	—	—	—	—	—	—
12' Chain	192½"	—	33¼	—	—	—	—	—	—
12' Screw	191¾"	34¼	—	—	—	—	—	—	—
14' Belt	216½"	—	31¼	—	—	—	—	—	—
14' Chain	216½"	—	36¼	—	—	—	—	—	—
14' Screw	215¾"	37¼	—	—	—	—	—	—	—